

LockMaster S2

High Security Swing Gate System to LPS 1175 B3 (SR2) Issue 8



Description

CLD's LockMaster S2 swing gates have been specially developed to blend in seamlessly with a CLD Securus fence line. Available using a Securus S2 infill panel, LockMaster S2 offers security rated access control, whilst maintaining aesthetics. Rigorously tested by the Loss Prevention Certification Board (LPCB) to guarantee a minimum delay of 3 minutes against attack, LockMaster S2 is also Secured by Design accredited, making it a police preferred specification for security.



Find out more
Scan for more information



Features

Matches CLD Securus fenceline

Double/single in/out opening

Security rated gates

Exploded view of post and fixing details for the CLD LockMaster S2
This product has additional features not demonstrated for security reasons



cld-systems.com


LockMaster S2

High Security Swing Gate System to LPS 1175 B3 (SR2) Issue 8

Product Technical Information

Standard	LPS 1175 BS1722-14:2017 BS EN ISO 141:2009 BS EN 13438:2013 Secured By Design
Description	Open mesh steel high security gate system with mesh infill, to match fencing
Panel Options	Panel infill to match CLD Securus S2
Panel Width	To suit mesh infill panels: Single leaf: 900mm minimum to 4000mm maximum. Double leaf: 1200mm to 8000mm maximum
Available Heights	Double 2440mm to 5000mm to match fence panel. Single 2440mm to 3000mm or up to 5000mm with lintel panel
Nominal heights	2.4m to 5.0m
Finish	Polyester powder-coated to match mesh infill. Any RAL colour
Post Dimensions	80mm x 80mm minimum
Foundations	Set posts in holes 450mm square x 950mm deep min. Note: Contractor/ client is responsible for the foundation size suitable for the ground conditions
Configuration	Double leaf/single leaf. Inward or outward opening as required
Gate Frame	To suit mesh infill panels: Vertical stiles: minimum of 50mm x 50mm x 3mm SHS Horizontal rails: minimum of 50mm x 50mm x 3mm SHS
Locking	Slide bar with certified padlock or key operated hook bolt lock
Hinges	3 x hinge sets with min M20 eye bolts
Warranty	Minimum of 15 years against manufacturing defects.
Notes	All dimensions are nominal, for further information please contact CLD Fencing Systems. Information is correct at time of production. As part of our policy of continuous improvement, we reserve the right to alter product specification without notice.

System Details



Disclaimer

Fencing should be installed in accordance with BS 1722-14. Every care has been taken to ensure that all information provided on this data sheet is accurate. CLD Fencing Systems Ltd reserves the right to change product specification at any time. Please ensure that you have the latest information which can be found on our website or by contacting our team.

Document Reference - CLD_LockMaster_S2_DS_20220223