

CLD FenceSafe-E

On-ground/temporary V-mesh profiled monitored pulse fence



Find out more
Scan for more information

Description

FenceSafe-E is the world's first temporary security fence with active monitored pulse fencing. Part of the revolutionary FenceSafe range of temporary rigid mesh fencing systems, it requires zero ground strike allowing rapid deployment anywhere around the globe. By utilising pre-assembled modular end, return and adjustable corners, the entire system can be installed in record time. In development trials over 30m of the system was installed and commissioned in under 90 minutes.



Features

Zero ground strike

Easy fixing security clips

Fully resistant welded joints with 5mm wires.

30mm projecting spikes

Exploded view of post and fixing details for the CLD FenceSafe-E
This product has additional features not demonstrated for security reasons

CLD FenceSafe-E

On-ground/temporary V-mesh profiled monitored pulse fence

Product Technical Information

Standard BS1722-14:2017

Panel Type	Available in three different mesh options, including Eclipse-60 profiled, Dulok-Lite double-wire and Securus-Lite 358 systems.
Panel Width	3000mm Eclipse-60, 2506mm Dulok-Lite, 2514mm Securus-Lite
Wire Diameter	Dependent on mesh type
Mesh size	Dependent on mesh type
Fixings	Dependent on mesh type
Available Heights	Dependent on mesh type
Nominal Heights	3.0m overall (with mesh to 2.0 or 2.4m)
Finish	Polyester powder-coated to 60-80 microns or 160-200 microns with marine grade and metallics. Any RAL colour available
Top Edge Projection	Nil
Panel installation	Bottom of panel maximum 40mm above ground
Topping Options	Options available on request
Posts	SHS, galvanised after manufacture and polyester powder-coated to match fencing
Post Dimensions	60mm x 60mm
Post Centres	3010mm Eclipse-60 2520mm Dulok-Lite 2440mm Securus-Lite
Foundations	Installation using CLD FenceSafe Base unit, with 4-way adjustable bracket and 200kg of ballast. System to be designed in accordance with BS6399-2 or BS EN 1991 for area of use.
Warranty	Fencing: Minimum of 15 years against manufacturing defects. Energisers: 7 years

System Details

Disclaimer

Fencing should be installed in accordance with BS 1722-14. Every care has been taken to ensure that all information provided on this data sheet is accurate. CLD Fencing Systems Ltd reserves the right to change product specification at any time. Please ensure that you have the latest information which can be found on our website or by contacting our team.

Document Reference - CLD_FenceSafe-E_20230704